CHICAGO APPROVED RECESSED STEEL EMERGENCY UNIT

Certification Information

LISTED

Catalog # Type		*Type*	
Project			
Comments		*Date*	
Prepared by			

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Battery pro rated for two years.
- Meets UL924, NFPA101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (20°C – 50°C).
- Meets City of Chicago emergency light and plenum requirements.

HOUSING

- Durable 20-gauge steel construction in white or black finish.

MOUNTING

- Knockouts on the back for wall mount.
- Side and top knockouts for conduit feed applications.

ILLUMINATION

- Two, 6V/12V 12.0 watt adjustable bi-pin halogen lamp heads provide optimal center-to-center spacing.
- Long lasting, efficient, wedge base incandescent or bi-pin halogen lamps.
- High performance chrome-plated metallized reflector and glass lens for optimal light distribution.

ELECTRICAL

- Dual 120V/277 voltage.
- Charge rate/power “ON” LED indicator light and push-to-test switch for mandated code compliance testing.
- LVD (low voltage disconnect) prevents battery from deep discharge.
- 6V Sealed lead acid, maintenance-free, rechargeable battery.
- Internal solid-state transfer switch automatically connects the internal battery to lamp heads for minimum 120-minute emergency illumination.
- • Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Remote capacity of 26W and 76W available on 50W and 100W models respectively.

ORDERING INFORMATION

ITEM NUMBER	VOLTAGE	WATTS (for 90 mins.)	HOUSING COLOR
IL-CADXR	6- 6V	5– 50	Blank- White
	12- 12V	10– 100	B– Black

Due to continuous improvements, the information herein may be changed without notice

DIMENSIONS