

Catalog # Type		Type
Project		
Comments		Date
Prepared by		

OPTIONS

- CW: Optional internal heater for extreme cold temperature applications (-30° C - 50° C).
- CEC: Certified to CEC under Title 20 Regulations.

WARRANTY / LISTING

- Five year warranty on all electronics and housing. Batteries prorated for two years
- Meets UL924, cULus, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
UL listed for Wet locations (20°C – 50°C).

HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

MOUNTING

- Universal knockout pattern on back plate for wall mount.
- Threaded opening at the top of the enclosure for conduit mount



Certification Information



ILLUMINATION

- Two fully adjustable ultra bright, round, 12W, MR-16 halogen lamp heads standard.

ELECTRICAL

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery (EM models only).
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.
- Self-diagnostic feature performs monthly, bi-annual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- Photocell control sensor included as standard for use as dusk-to-dawn luminaire.
- Field-selectable wiring allows for AC operation of unit to be controlled using a wall-switch, photocell or other switching mechanism.

ORDERING INFORMATION

ITEM NUMBER	HOUSING COLOR	STANDARD FEATURE	OPTIONS	STANDARD FEATURE
IL-DBEL-ACEM-HL	W- White	SDT- Self Diagnostics	CW- Cold Weather	PC- Photocell Sensors
	B- Black		CEC- Title 20 Compliant	
	BR- Dark Bronze			
	N- Nickel			

DIMENSIONS

